



Superior Performance Simplifying Industrial Applications with Reliable Durability

CipherLab's 2500 series scanner instantly updates your business data collection process with a 578 scan rate, IP54 rating, 1D/2D reader option, and automatic cable detection. It seamlessly combines its superior scanning performance with business-rugged designs. Additionally, the 2500 series scanner provides easy deployment and corded/*Bluetooth*® connections for users to enjoy. More than just these advantages, its enhanced ESD (electrostatic discharge) protection, built-in removable battery and other user-friendly features help take your scanning experience to new and higher levels.



The 2500 series 1D and 2D scanner is a device built with superior scanning capabilities that provide easy operations. It features a high-speed read rate of a snappy 578 scans per second on 1D barcodes. For small-item applications, the 2500 series has the ability to read high-density 1D barcodes up to 3-mil and 2D barcodes up to 5-mil on tiny objects. Built with a scan beam of 3mm in width from 15 cm away, the 2500 series eases its aiming for scanning and prevents the probabilities of misreads. The thin scan beam works extremely well when barcodes are placed close to each other. On top of it all, it is capable of reading low contrast images, such as barcodes that are poorly printed or printed on reflective surfaces, down to PCS (Print Contrast Signal) 15%. Another important advantage the 2500 series possess is the ability to scan barcodes shown on mobile phones. With these advantages, CipherLab 2500 series users can easily collect data with all of its superior and up-to-date scanning resources.



The CipherLab 2500 scanner has been thoroughly tested for its durability. It has passed the IP testing and rated a durable IP54 that is dust protected and able to sustain water splashing. These features come in handy with harsher conditions of high humidity. The 2500 series also has a 1.8m drop resistance that offers continuous functionality without the stressful worries of accidental falls onto rough surfaces.







Moreover, the device comes with an optional tether plate and wrist strap which enables users to attach the device to a mounting bracket or around the user's wrist. All of the 2500 series' durability is ultimately coupled with comfortable operational designs to create a productive experience for its users.

Easy Deployment Generate Faster Workflow

CipherLab's 2500 series 1D and 2D scanners are built with the intentions of fast and easy deployments for its users. It features the capabilities for users to connect their host systems by using USB, RS232 and keyboard wedge interface cables. With the appropriate interface cable connected to a computer, the 2500 series can automatically detect the cables and allow the users to easily access the information acquired.

User Friendly Features of the 2500 Series

The CipherLab's 2500 series provide flexibility for its users with its features. It comes with a built-in *Bluetooth®* that keeps the device connected to a computer up to a line-of-sight distance of 100 meters. The *Bluetooth®* scanner users can easily move around its working area while still being connected. Its built-in removable battery can easily provide 24 hours of continuous work and offer an ideal solution for businesses that need extended hours of operations.

Its enhanced ESD (electrostatic discharge) protection can handle up to ± 10 kV(contact), ± 20 kV (air) of ESD surge which protects sensitive electronic damages caused by electronic discharge events. Simply put, the CipherLab 2500 series is a durable device with superior features that will update your business to new grounds.













Business-Rugged	Handheld Scanner
-----------------	------------------

Model		2500	2560	2504MR	2564MR	
iviouei		Linear			nager	
Category		Corded	Bluetooth® V4.0 Dual mode (2.1 + EDR/ BLE)	Corded	Bluetooth® V4.0 Dual mode (2.1 + EDR/ BLE)	
RF Communication of Bluetooth®-Scanner	Coverage ¹		100 m ¹ / 295 ft. line of sight		100 m ¹ / 295 ft. line of sight	
	Standard profile		SPP, HID, GATT		SPP, HID, GATT	
Performance	Optical sensor	2500 pixels		1280x960 pixels		
	Light source	Red LED 625 nm (2X)		Warm White LEDs (2x)		
	Resolution	3 mil		3 mil- 1D barcode / 5 mil - 2D barcode		
	Depth of field	3 mil : 2.5 to 8 cm 13 mil : 1.5 to 50 cm 20 mil: 25 to 75 cm		Code 128 5 mil : 18.5 to 37.5 cm PDF 417 5 mil : 21 to 26.5 cm Data Matrix 7.5 mil : 17 to 35 cm Data Matrix 10 mil : 15.5 to 45.5 cm UPCA 13 mil : 8 to 94 cm Code 39 100 mil : 28 to 425 cm Data Matrix 160 mil : 29.5 to 384 cm		
	Scanning angle	Pitch ± 70° Skew ± 70°		Pitch ± 60°, Skew ± 60°		
	Minimum PCS	15%		25%		
	Scan rate	578 scans/ second		60 scans/second		
	Ambient illumination	100,000 lux				
	Hands-free scanning	Auto-sense and continuous modes		Auto-sense and presentation modes		
	Barcodes support	Codabar, Code 39, Code 93, Code 128, GS1 DataBar (RSS), Industrial 2 of 5, Interleave 2 of 5, ISBT-128, Italian and French Pharmacodes, Matrix 2 of 5, MSI, Plessey, Telepen, UPC/EAN/GS1-128, and more		1D: All of the bacodes that 2500 series 1D scanners can support 2D: PDF417, MicroPDF417, Data Matrix, QR code, Micro QR Code, Aztec, MaxiCode, Composite Codes, TLC-39		
	Programmable features	Data editing, interface selection, symbology configuration				
	Language support	US and UK English, French, Italian, Belgian, Norwegian, Swedish, Spanish, Portuguese, German, Swiss German, Japanese, Turkish, Hungarian, Danish				
Physical	Dimension LxWxH	96.2 x 66x160.5 mm				
	Weight (without cabe/ with battery)	145 g / 4.9 oz.	185g / 6.5 oz.	166 g / 5.9 oz.	198g / 7.0 oz.	
	Color	Black, Register White				
	Switch	Tactile Switch				
Electrical	Memory for Bluetooth®scanner reserver buffer / batch mode		64 K / 256 K		10 K / 4 MB	
	Working hours for Bluetooth®-Scanner		60 hours based on 1 scan / 5 seconds		25 hours based on 1 scan / 5 seconds	
	Voltage	3.7 V 800mAh Li-ion battery				
	Power consumption ² Standby / Operating	20 mA / 255 mA	12 mA / 250 mA	16 mA/ 270 mA	17 mA/ 280 mA	
User Environment	Temperature	Operating: 0 °C to 50°C / 32°F to 122°F Storage: -40°C to 70°C / -40°F to 158°F (w/o battery)				
	Humidity	Operating: 10% to 90% Storage: 5% to 95%				
	Impact resistance	1.8 m mutliple drops onto concrete, 1000 (1 m) tumbles				
	Ingress protection	IP54				
	Electrostatic discharge		±10 kV conta	ct ±20 kV air		
	Regulatory compliance	FCC, IC,CE, RCM, BSMI, KC	FCC, IC, CE, RCM, BSMI, NCC, KC, SRMC	FCC, IC,CE, RCM, BSMI, KC	FCC, IC, CE, RCM, BSMI, NCC, KC, SRMC	
			REACH, WEEE, ErP, Eurpoe Ro	oHS, Taiwan RoHS, China RoHS		
Configuration		Setup options include Windows®-based ScanMaster software				
Accessories		USB, RS232 and keyboard wedge Communication cradle with battery charger option(<i>Bluetooth</i> ® connections)		cables, hands-free adjustable stand ction up to 7 scanners), single battery charger for <i>Bluetooth</i> ® scanner		
Warranty		5 year		3 year (engine 1 year)		
				, , , , ,		



HEADQUARTERS CipherLab Co., Ltd. 12F, 333 Dunhua S. Rd., Sec.2 Taipei, Taiwan 10669 Tel +886 2 8647 1166 Fax +886 2 8732 3300 www.cipherlab.com CipherLab Electronics Trading (Shanghai) Co., Ltd. J Room, 4F, No.728 West Yan'an Road, Changning District, Shanghai China 200050 Tel +86 21 3368 0288 Toll Free 400 920 0285 Fax +86 21 3368 0286 CipherLab USA Inc. 2552 Summit Avenue STE 400 Plano, Texas, USA 75074 Tel +1 469 241 9779 Toll Free 888 300 9779 Fax +1 469 241 0697

CipherLab Europe Flight Forum 40, 5657 DB Eindhoven, The Nederlands Tel + 31 (0) 40 2951510